

Material Safety Data Sheet

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PT Maxnitron Racer Axle SAE 80W-90

Product Use: Passenger Car Engine Oil
Company Identification: **PTG Energy Public Company Limited**
90 CW TOWER A (33rd Floor),
Ratchadaphisek Rd., HuayKwang, HuayKwang,
Bangkok, Thailand 10310
Emergency Call: 0-2168-3377, 0-2168-3388
Website: <https://www.ptgenergy.co.th/> ;
<http://www.ptgenergy.co.th/ptmaxnitron/>

SECTION 2 : HAZARDS IDENTIFICATION

2.1. GHS classification of the substance or mixture

2.1.1. According to Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 3rd Revised Edition":

Product: Mixture

Physical Hazards	Not classified
Health Hazards	Not classified
Environmental Hazards	Not classified

2.1.2. Additional information:
None

2.2. GHS label elements

Labelling according to GHS 3rd Revised Edition

Hazard Pictogram

Not applicable

Signal word

Not applicable

Hazard statements

Not applicable

Precautionary statements

Not applicable

2.3. Other hazards which do not result in GHS classification

None known

Revision Number:	0	Product Name:	PT Maxnitron Racer Axle SAE 80W-90
Revision Date:	2-July-2025_PP		

SECTION 3 : COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Mixtures or substances

Mixtures of highly purified base oil and lubricating oil additives.

Chemical identity	CAS Number	Concentration (% weight)	Ingredients hazard code
Olefin polysulphide	Trade secret	< 2	H317 , H400 , H410
Alkyl phosphorous acid esters	Trade secret	0.2 - 2	H317

* Remaining ingredients which within the current knowledge of the supplier are not classified as hazardous to health or the environment, or below the applicable cut-off concentration, and hence do not require disclosure in this section as according to GHS.

SECTION 4 : FIRST AID MEASURES

4.1. Description of first aid measures

General advice:	Treat according to symptoms.
Skin contact:	Rinse with soap and plenty of water and remove contaminated clothing and shoes.
Inhalation:	Remove to fresh air. No specific first aid measures are required.
Eye contact:	Rinse immediately with running water, also under the eyelids for 15 minutes. Check for and remove any contact lenses.
Ingestion:	Wash out mouth with water. Remove dentures if any. Drink glasses of water or milk to dilute. If any symptoms appear get medical treatment. Do not induce vomiting.
Protection of first-aiders:	Wear personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

No effect expected.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically.

SECTION 5 : FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media:

Alcohol resistant foam. Water fog. Carbon dioxide (CO₂). Dry chemical powder, sand or earth may be used for small fires.

Revision Number:	0	Product Name:	PT Maxnitron Racer Axle SAE 80W-90
Revision Date:	2-July-2025_PP		

Unsuitable extinguishing media:

Do not use water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire hazardous decomposition products may be produced such carbon monoxide, carbon dioxide, phosphorus (POx), sulfur oxides (SOx), hydrogen sulfide (H₂S) and other pyrolysis products typical of burning organic material.

5.3. Special protective equipment and precautions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity. Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Put on appropriate personal protective equipment. Do not touch or walk through spilled material.

6.2. Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Collect spillage. Report spills to local authorities as appropriate or required.

6.3. Methods and materials for containment and cleaning up

Stop leak if without risk. Spills can be reused or recycled if possible. Absorb spills in special absorbents or inert materials such as diatomite or vermiculite and collect in suitable container for disposal. Dispose of as special waste in compliance with local and national regulations. Prevent further leakage or spillage if safe to do so.

SECTION 7 : HANDLING AND STORAGE

7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Use and handle in well ventilated areas. Use personal protective equipment as required. Keep away from heat and ignition sources. Handle in accordance with good industrial hygiene and safety practise. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.

Empty containers retain product residue and can be hazardous. Do not reuse container. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.2. Conditions for safe storage, including any incompatibilities

Store under cover away from moisture and sources of ignition. Do not overheat in storage. Keep container tightly sealed.

Revision Number:	0	Product Name:	PT Maxnitron Racer Axle SAE 80W-90
Revision Date:	2-July-2025_PP		

SECTION 8 : EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

National occupational exposure limits / Biological occupational exposure limits:

Components	TWA
Hydrotreated heavy paraffinic distillate	MOL : 0.8 mg/m ³ (TWA)

Recommended monitoring procedures

Not required under sufficient ventilation.

8.2. Appropriate engineering controls

General ventilation should be designed to prevent accumulation and recirculation in the workplace.

8.3 Individual protection measures, personal protective equipment

Handle in accordance with good industrial hygiene and safety practise.

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

Eye protection:

Wear safety glasses with side shields, goggles or face shield.

Protective clothing:

Wear suitable protective clothing and chemical resistant gloves which includes nitrile rubber gloves, etc.

Ventilation:

Provide adequate ventilation when processing material at elevated temperatures.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance:	Liquid
Colour:	Amber to brown
Odour:	Characteristic
Odour Threshold:	No data available
pH:	Not applicable
Melting point/ freezing point (°C):	No data available
Boiling point (°C):	No data available
Flash point, COC (°C):	242
Evaporation rate:	No data available
Flammability (solid, gas):	No data available
Lower explosion limit:	No data available
Upper explosion limit:	No data available

Revision Number:	0	Product Name:	PT Maxnitron Racer Axle SAE 80W-90
Revision Date:	2-July-2025_PP		

Vapour pressure:	No data available
Vapour density:	No data available
Density (g/cm ³):	0.8788 (15°C)
Solubility:	Not soluble in water
Partition coefficient: n-octanol/water:	No data available
Autoignition temperature (°C):	No data available
Decomposition temperature (°C):	No data available
Viscosity, kinematic (mm ² /s):	130.8 (40°C)

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4. Condition to Avoid

Extremes of temperature and direct sunlight.

10.5. Incompatible materials:

May react with strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

10.6. Hazardous Decomposition Products

Incomplete combustion will generate smoke, toxic fume, carbon dioxide and hazardous gases, including carbon monoxide. Hydrogen Sulfide (Temperatures > 65°C)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on the likely routes of exposure

11.2 Symptoms related to physical, chemical and toxicological characteristics

Skin contact

No effect expected.

Eye contact

Mild discomfort.

Inhalation

No significant effect expected.

Revision Number:	0	Product Name:	PT Maxnitron Racer Axle SAE 80W-90
Revision Date:	2-July-2025_PP		

Ingestion

Discomfort.

Carcinogenic effects

Based on available data, the classification criteria are not met.

Mutagenic effects

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.3 Delayed and immediate effects and also chronic effects from short- and long-term exposure

Effect on the skin - irritation.

11.4 Numerical measures of toxicity

Components	LD50/oral	LC50/inhalation/rat	LD50/dermal/rabbit
Highly purified base oil	LD50 > 15000 mg/bw	LC50 2.18 mg/m ³ /4h	LD50 >5000 mg/bw

SECTION 12 : ECOLOGICAL INFORMATION
12.1. Eco-Toxicity (aquatic and terrestrial)

Components	Type	Freshwater Fish Species	Test Method
Highly purified base oil	96 hr LC ₅₀	No data available	-

Components	Type	Freshwater Fish Species	Test Method
Highly purified base oil	48 hr EC ₅₀	No data available	-

Components	Type	Freshwater Fish Species	Test Method
Highly purified base oil	96 hr EC ₅₀	No data available	-

12.2. Persistence and degradability

Expected to be readily biodegradable but the product contains components that may persist in the environment.

Revision Number:	0	Product Name:	PT Maxnitron Racer Axle SAE 80W-90
Revision Date:	2-July-2025_PP		

12.3. Bioaccumulative potential

Product is not likely to accumulate in biological organisms.

12.4. Mobility in soil

The product will absorb to the soil particles and will not be mobile.

12.5. Other adverse effects

Films formed on water may affect oxygen transfer and damage organisms.

SECTION 13 : DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods****Waste from residues / unused products:**

Reuse or recycle whenever possible. If not, dispose of in accordance with hazardous waste management regulations of the country of use.

Contaminated packaging:

Empty containers should be taken for local recycling, recovery or waste disposal in accordance with hazardous waste management regulations of the country of use.

Relevant regulation:

Hazardous waste management regulations of the country of use.

SECTION 14 : TRANSPORTATION INFORMATION**14.1. UN-Number**

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing group

Not regulated

14.4.1. Further information for transport**IMDG**

Not regulated

ADR/RID

Not regulated

Revision Number:	0	Product Name:	PT Maxnitron Racer Axle SAE 80W-90
Revision Date:	2-July-2025_PP		

ICAO/IATA

Not regulated

14.5. Environmental hazards:

None.

14.6. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

Not evaluated.

14.7. Special precautions for user

None required.

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

This product is not considered as hazardous according to the classification criteria of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 3rd Revised Edition.

Further Information:

This SDS is prepared for the purpose of providing safety information for transportation and occupational handling conditions.

SECTION 16 : OTHER INFORMATION**This safety data sheet has been prepared according to following regulations:**

Local regulations adopting Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 3rd Revised Edition.

Hazard statements:

H360 : May damage fertility or the unborn child

Revision 3

Issued Date: 05.10.2022

SDS prepared by: P.S.P. Specialties Public Company Limited

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, processing, storage, transportation, disposal and accidental release and is not to be considered a warranty or quality specification. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. We do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of, or in any way connected with the handling, storage, use, or disposal of this product.

Revision Number:	0	Product Name:	PT Maxnitron Racer Axle SAE 80W-90
Revision Date:	2-July-2025_PP		